



# MiniFlow CC

THE EFFICIENT EXTENSION OF YOUR MACHINE



# MiniFlow CC

The HORSCH MiniFlow can be flexibly mounted on almost all machines. Depending on the working width and the range of applications, the number of outlets and distribution versions can be adapted to the respective purpose. This provides an ideal addition to existing systems.

- Compact design
- Easy to use
- Application technology for liquid substances



Control panel MiniFlow 800 CC



MiniFlow 800 CC Transformer 9 VF



Compact design

## TECHNICAL DATA

MiniFlow CC	800 CC (Solo)
Empty weight (kg)	245
Fresh water tank (l)	80
Piston diaphragm pump (l/min)	133
Mounting dimensions Length x Width x Height (m)	1,5 x 1,05 x 1,5
Filling height solo (m)	1,45
Additional weight (kg)	290
Mixture tank nominal volume (l)	800

Mixture tank actual capacity (l)	720
Hand wash tank (l)	18
Filling height (m)	1,4
Dimensions of the feed openings (m)	0,29
DA control devices	1
Depressurised return flow (max. 5 bar)	1
Oil quantity hydr. fan (l/min)	15 - 20

Your distributor



**HORSCH Maschinen SE & Co. KG**

Sitzenhof 1 · 92421 Schwandorf

Phone: +49 9431 7143-0

Fax: +49 9431 7143-9200

E-Mail: [info@horsch.com](mailto:info@horsch.com)

**[horsch.com](http://horsch.com)**

Paper: 120 g/qm Maxi Offset. The paper is certified according to the EU Ecolabel. This label is only granted for products and services whose environmental consequences are considerably lower than those of comparable products. For more details see [www.eu-ecolabel.de](http://www.eu-ecolabel.de). Printing ink: Printing ink QUICKFAST COFREE. Free from mineral oil and cobalt. Moreover, it is certified and recommended for printing according to the „Cradle-to-Cradle“ principle (quasi “from the origin back to the origin”) – an approach that deals with the spreading of continuous and consequent recycling management. More details at [www.c2c-ev.de](http://www.c2c-ev.de).

All specifications and diagrams are approximate and not binding. Technical features and design are subject to change.

EN-60212000 (AGRI25)